



Aristomat GL / TL

NEW

Powerful
Routing Device

HF spindle with 1.000 W and 60.000 rpm



As **Stand-alone tool** or in **Combination**
with other tool heads, e.g. MultiHead IV

ARISTO

ARISTO Graphic Systeme
GmbH & Co. KG.

Powerful Routing Device for the processing of all nonmetallic materials

Specifications

3-phase asynchronous motor HF spindle

- Speed : 0 - 60.000 rpm, adjustable via pc software *ARISTO Cutter Control Panel*
- Torque : max. 30 Ncm (dependent on the cooling system)
- Direction of rotation : anticlockwise
- Power : max. 1000 W (dependent on the cooling system)
- Bearing system : ceramic, 3-precision bearings with lifetime lubrication
- Tool change : manually
- Sealing air : 0.5 - 0.8 bar
- Collets : 1.5 - 6.35 mm
- Ambient conditions : + 5° C up to + 40° C, max. 2000 m N.N

Regulated Z-axis

- Lift : 50 mm electrically / pneumatically
- z-position adjustable via pc software *ARISTO Cutter Control Panel*
- Chip exhaust unit to connect to an industrial vacuum cleaner

Recommended industrial vacuum cleaner (optionally available)

Nilfisk Advance GB 726-L with Gore-Filter and sound damping cover

- Power : 2.2 kW
- Tank capacity : 46 l
- Air flow : 86 l/s
- Suction hose : 38 mm diameter
- Power-On : ARISTOMAT controlled



ARISTO
ARISTO Graphic Systeme
GmbH & Co. KG.

Schnackenburgallee 117
D-22525 Hamburg/Germany
Tel.: +49-40-547 47- 0
Fax: +49-40-547 47- 111
e-mail: sales@aristo.de
www.aristo.de

ARISTO GRAPHIC SYSTEME
Ges.m.b.H.
Jakob Prandtauer Str. 1
A-6300 Wörgl/Austria
Tel.: 0043-53 32-76 22 9-0
Fax: 0043-53 32-76 22 9-77
e-mail: info@aristographic.at

INTEGRAL TECHNOLOGIE SARL
8/10 rue du Bois Sauvage Bât i
F-91055 Evry Cedex/France
Tel.: 0033-1-64 97 81 82
Fax: 0033-1-64 97 81 86
e-mail: IntegralTe@aol.com